

LIS009409810B2

(12) United States Patent

Lehmann et al.

(54) METHOD FOR PRODUCING SYNTHETIC OUARTZ GLASS GRANULES

(71) Applicant: Heraeus Quarzglas GmbH & Co KG

(72) Inventors: Walter Lehmann, Leipzig (DE);

 $\textbf{Thomas Kayser}, Leipzig\ (DE)$

(73) Assignee: Heraeus Quarzglas GmbH & Co. KG,

Hanau (DE)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/390,991**

(22) PCT Filed: Mar. 20, 2013

(86) PCT No.: **PCT/EP2013/055772**

§ 371 (c)(1),

(2) Date: Oct. 6, 2014

(87) PCT Pub. No.: WO2013/149831

PCT Pub. Date: Oct. 10, 2013

(65) Prior Publication Data

US 2015/0059407 A1 Mar. 5, 2015

(30) Foreign Application Priority Data

Apr. 5, 2012 (DE) 10 2012 006 914

(51) Int. Cl.

C03B 20/00 (2006.01) **C03B 19/09** (2006.01)

(Continued)

(52) U.S. Cl.

(Continued)

(58) Field of Classification Search

CPC C03B 20/00; C03B 19/095; C03B 19/107; C03B 19/1095; C03B 19/1005; C03B 2201/02; C03B 2201/03

See application file for complete search history.

` '

(10) **Patent No.:**

(56)

(45) **Date of Patent:**

References Cited U.S. PATENT DOCUMENTS

US 9,409,810 B2

Aug. 9, 2016

3,775,077 A 11/1973 Nicastro, Jr. et al.

(Continued)

FOREIGN PATENT DOCUMENTS

DE 102004038602 B3 12/2005 DE 102005045051 A1 3/2007

(Continued) OTHER PUBLICATIONS

Machine translation of DE 10 2004 038 602, Werdecker et al., Process for making quartz glass for use in the manufacture of lamps and semiconductors involves melting glass by electrically heating in a vacuum, the glass containing a specified concentration of temperature-stable hydroxyl groups, Dec. 29, 2005.*

(Continued)

Primary Examiner — Queenie Dehghan (74) Attorney, Agent, or Firm — Tiajoloff & Kelly LLP

(57) **ABSTRACT**

The production of quartz glass granules comprises the granulation of pyrogenically produced silicic acid and the formation of a SiO₂ granulate (9), the drying and cleaning of the SiO₂ granulate (9) by heating in an atmosphere containing halogen, and the vitrification of the SiO₂ granulate (9) under a treatment gas which contains at least 30% by volume of helium and/or hydrogen. This process is time-consuming and expensive. In order to provide a method which, starting from a porous SiO₂ granulate (9), allows the cost-effective production of dense, synthetic quartz glass granules suitable for melting bubble-free components of quartz glass, the invention proposes that the cleaning and vitrification of the SiO₂ granulate (9) and a post-treatment of the vitrified quartz glass granules are carried out in each case in a rotary tube (6) of a rotary kiln (1), said rotary tube rotating about a central axis (7), wherein the rotary tube (6) comprises an inner wall made of a ceramic material during vitrification, and wherein the vitrified quartz glass granules are subjected to a post-treatment during a treatment period of at least 10 minutes in an atmosphere which contains less than 20% of helium or hydrogen at a treatment temperature of 300° C. or more.

24 Claims, 1 Drawing Sheet

